

- ✔ Combination alarm offers protection from the dangers of smoke and from carbon monoxide poisoning in a single unit
- ✔ Battery operated (9V battery supplied as standard).
- ✔ Photoelectric smoke alarm sensing technology
- ✔ Front-loading battery compartment for added ease of use and convenience
- ✔ Test/Reset Button. Tests the alarm circuit operation and allows the alarm to be silenced immediately.
- ✔ Sophisticated 'Voice Message System' not only tells you which danger has been detected, but can even notify you of an historical event, such as "Caution, Carbon Monoxide Previously detected."
- ✔ End of Life Warning Signal - Alerts user when it's time to replace the alarm (after 10 years protection)
- ✔ HUSH control feature that can be used to silence nuisance alarms



10SCO

Product Description

The Kidde 10SCO battery operated combination smoke and carbon monoxide alarm offers protection from the dangers of smoke and carbon monoxide in a single unit for added convenience.

The 10SCO has a unique voice alarm to help you to determine which danger has been detected - "Warning Carbon Monoxide" or "Fire Fire" will be said from the alarm.

These alarms have a fixing bracket and they are designed to be wall or ceiling mounted in the home. They have a 10-year sensor life.

Carbon monoxide is a colourless, tasteless and odourless gas that is produced when fossil fuels such as coal, oil, natural gas, LPG, charcoal and wood are not burned efficiently. It can be produced from poorly maintained or badly fitted domestic heating appliances such as boilers, wall heaters, wood burners, blocked flues or exhaust vents.

The symptoms of CO poisoning include headaches, sickness, tiredness and muscle pain - all of which can easily be misdiagnosed as flu. It is therefore important to protect your family and home with a carbon monoxide alarm.



Order Code	10SCOC
Power Supply	9V Battery
Smoke Alarm / CO Technology	Sensor Technology' Smoke (Photoelectric), CO (Electrochemical)
Temperature Range	40°F (4°C) to 100°F (38°C) and -10°C to +60°C for storage or transport
Humidity Range	10%-95% relative humidity (RH)
Alarm Dimensions	145mm x 145mm x 45mm
Alarm Weight	0.38kg
Life of Alarm / Warranty	10-year sensor life and warranty
Approvals	Approved by BSI to EN52091 (CO) and EN14604 (Smoke)
Dimensions (in-pack)	282mm x 189mm x 45mm
Weight (in-pack)	0.44kg
UPC Barcode	0-047871-104062
Case Quantity	3
Case Dimensions	202 x 158 x 296mm
Case Weight	1.4kg
ITF Outer Code	100-47871-10406-9

