



EN Technical data

Contains fluorinated greenhouse gases. Hermetically sealed equipment.

	FreshJet 1100	FreshJet 1700	FreshJet 2200	FreshJet 2700	FreshJet 3200
Compressor cooling capacity:	1000 W	1700 W	2200 W	2500 W	2800 W
Cooling capacity based on ISO 5151:	850 W	1600 W	2050 W	2500 W	2800 W
Heating capacity:	–	800 W	1200 W	3300 W	
Rated input voltage:	230 V~ / 50 Hz				
Power consumption in cooling mode:	2.0 A	2.7 A	4.1 A	5.2 A	5.7 A
Required fuse:	3 A	4 A	5 A	10 A	10 A
Power consumption in heating mode:	–	3.5 A	5.2 A	5.9 A	5.9 A
Required fuse:	–	4 A	6 A	10 A	10 A
Operating temperature range:	0 °C to +52 °C				
Refrigerant:	R-134a	R-407c	R-407c	R-407c	R-410a
Refrigerant quantity:	0.280 kg	0.545 kg	0.520 kg	0.875 kg	0.735 kg
CO ₂ equivalent:	0.4004 t	0.96683 t	0.92248 t	1.55225 t	1.53468 t
Global warming potential (GWP):	1430	1774	1774	1774	2088
Protection class:	IPX4				
Max. volume of space in the vehicle (with insulated walls):	16 m ³	20 m ³	25 m ³	29 m ³	
Noise emission:	<70 dB(A)				
Dimensions L x W x H (height above vehicle roof):	787 x 562 x 225 mm			980 x 650 x 248 mm	
Weight:	approx. 22.5 kg	approx. 29 kg	approx. 32 kg	approx. 39 kg	approx. 36 kg
Inspection/certification:					

For the current EU declaration of conformity for your device please refer to the respective product page at dometic.com or contact the manufacturer directly (see back page).